



EnyGy® enyCell Series, Module Type (Electric Double Layer Capacitors)

Datasheet EC6R015508020M

- Endurance: 6.0V 65°C 1000 hours
- High capacitance and small size
- Low ESR
- Long cycle life
- Contains UL-Recognized cell components
- RoHS compliant



Specifications

Part Number	EC6R015508020M	
Rated Voltage	V	6.0
Capacitance	F	1.5
ESR, 1kHz	mΩ	90
ESR, DC	mΩ	150
LC(72hr)	mA	0.015
Specific Energy	Wh/kg	2.50
Specific Power	kW/kg	20.00
Max. Peak Current	A	3.67
Weight	g	3.00

1. Capacitance and Equivalent Series Resistance (ESR) measured according to IEC62391-1 at +25°C, with current in millamps (mA) = $10*C$
2. Leakage Current at 25°C after 72 hour charge and hold
3. Specific Energy (Wh/kg) = $(\frac{1}{2} * C * V^2 / 3600) / \text{weight}$
4. Specific Power (kW/kg) = $(V^2 / 4 * ESR) / \text{weight}$
5. Max Peak Current in Amps (A), 1 second discharge from rated voltage to half rated voltage = $(\frac{1}{2} * C * V) / (1 + ESR * C)$

Characteristics

Operating Temperature Range	-40 ~ +65°C	
Rated Voltage	6.0 VDC	
Capacitance Tolerance	-10% ~ +20%	
Temperature Characteristics	Capacitance change	Within $\pm 5\%$ of initial value at +25°C
	Internal resistance	Within $\pm 50\%$ of initial value at +25°C
	Duration	1000 hours
Endurance	Capacitance charge	Within $\leq 30\%$ of initial value
	Internal resistance	Within $\leq 100\%$ of initial specified value
Shelf Life	After 1000 hours no load test same as endurance	
Lifetime at RT ⁽¹⁾	10 years	
Cycle Life(25°C) ⁽²⁾	500,000 cycles	

(1) $|\Delta C| \leq 30\%$ of initial value and $|ESR| \leq 100\%$ of initial specified value.

(2) Cycle : between rated voltage and half rated voltage under constant current at 25°C.

Dimensions Unit:mm

L	22.0
W	16.0
D	8.5
P	Type-C 4.9
	Type-S 12.0
	Type-H 8.5
Φd	0.6
Single Cell Size	ΦD x L 8 x 20

